

### Description

The Pli-Dek Grout Tape is an all-purpose fiberglass reinforced paper backed strapping tape with pressure-sensitive natural rubber/resin adhesive. Medium-tensile strength, high adhesion and medium-impact.

### Uses

The grout tape is intended to be used as a component to the Pli-Dek waterproofing systems.

### Available Sizes

- 3/4" x 60 yds.
- 3/8" x 60 yds.
- 1/2" x 60 yds.
- 1/4" x 60 yds.

### Available Color

Natural

### Coverage

Coverage rate will vary based on job conditions

### Technical Information

<b>Backing</b> .....	Medium Crepe Paper
<b>Adhesive</b> .....	Natural Rubber/ Resin
<b>Reinforcement</b> .....	Fiberglass
<b>Tensile Strength</b> .....	198 lbs/in
<b>Elongation</b> .....	4% at Break
<b>Total Thickness</b> .....	.9.8 mils
<b>Operating Temperature Range</b> .....	32 to 200 F

### Storage

Protect from freezing. Do not store container in direct sunlight.

### Limitations

Not recommended for below grade. Do not apply to frost covered surfaces, or below 13°C (55°F). Do not apply if rain is expected in 24 hours and it must remain over 13°C (55°F) temperature for 24 hours.

### Clean-Up

Wash hands with warm water and soap.

#### *Disclaimer:*

*This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek Systems, Inc. to be accurate. Pli-Dek Systems, Inc. does not assume any legal responsibility for use or reliance on the information supplied here.*

