

Description:

The Pli-Dek Thin Drain is a 3-dimensional composite drainage system designed for applications that have a limited "height tolerance". Many indoor and outdoor thin-set applications must maintain a limited height tolerance due to door swings or to match up to other floor surfaces.

Applications:

- Outdoor Patios, Decks & Terraces
- Bathroom Floors, Showers, Kitchens, Foyers & Sun Rooms
- Underlayment for Carpet Applications on Concrete Floors
- Horizontal Applications with Limited Height Restrictions

Features:

- Easy Installation
- Creates Air Void Under Tile for Drainage
- Ultra Low Profile- 1/8" Core Thickness
- Protects Membrane
- Made in USA
- Filter Fabric Prevents Clogging

Specifications:

PD Thin Drain:

The Pli-Dek Thin Drain only adds 1/8" to the total thickness of thin-set application while allowing for the easy collection and removal for water and/or moisture.

Availability:

Technical Information:

Core	
Thickness	0.125 in.
Width	48 in.
Length	100 ft.
Compression	15,000 psf
Flow Rate	7 gal/min/ft.

Fabric	
Grab Tensile	100 lbs.
AOS	70 U.S. Sieve
CBR Puncture	250 lbs.
Flow Rate	140 gal/min/ft ²



Technical Assistance:

Contact Pli-Dek Systems, Inc. for any job specific questions.

Disclaimer:

This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek Systems, Inc. to be accurate. Pli-Dek Systems, Inc. does not assume any legal responsibility for use or reliance on the information supplied here.

