



NOTES:

- CONSIDERATION MUST BE MADE IN REGARDS TO THE HEIGHT OF THE SHEET METAL FLASHING AT THE WALL TO DECK JUNCTION IN ORDER TO ALLOW THE SLOPING MIX TO REMAIN A MINIMUM OF 2" BELOW THE WEEP SCREED.
- WHEN USING IN CONJUNCTION WITH CON-DEK SYSTEM, APPLY SLOPE MATERIAL PRIOR TO INSTALLATION OF FIBERGLASS AND PD RESIN (2 COATS).
- CRICKET LOCATION VARIES ACCORDING TO DRAIN/SCUPPER LOCATIONS.
- REFER TO PLI-DEK APPLICATION INSTRUCTION AND SPECIFICATIONS FOR INSTALLATION GUIDELINES.

DETAIL-ENCLOSED DECK LOW WALL DRAINS & SCUPPER-CONCRETE SUBSTRATE

SCALE: N.T.S.



41610 Date St., Suite 104 * Murrieta, CA. 92562
Phone: 800.364.0287 * Fax: 951.834.9555
WWW.PLIIDEK.COM

These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System:		Con-Dek System by PLI-Dek Systems, Inc. ICC-ES ESR-2097	
Detail:		ENCLOSED DECK LOW WALL DRAINS & SCUPPER CONCRETE SUBSTRATE	
Job:		Drawing Number:	
Date:	05-3-2013	CD-10	
Dwn:	H.K		