

MIN. 26 GAUGE
GALVANIZED SHEET
METAL FLASHING
(3/16" RISE)
(BONDERIZED)

4"

4"

3/4 OZ. FIBERGLASS & PD RESIN
(CONTACT PLI-DEK FOR
REQUIREMENTS)

GU80 BASE COAT

GU80 TOP COAT

GS88 PIGMENTED SEALER

SLOPED DECK

2.5 GALVANIZED METAL LATH

5/8" MIN. EXPOSURE 1 SHEATHING
(3/4" RECOMMENDED). SLOPE
1/4" PER 12"

NAILER OR EXTEND PLYWOOD
OVER EXTERIOR FINISH

STRUCTURAL FRAMING
(BY OTHERS)

FERRULE &
FASTENER
(BY OTHERS)

GUTTER
SLOPED TO DRAIN
(BY OTHERS)

STUCCO FINISH
(BY OTHERS)

DETAIL-FASCIA METAL TO GUTTER

SCALE: N.T.S



41610 Date St., Suite 104 * Murrieta, CA. 92562
Phone: 800.364.0287 * Fax: 951.834.9555
WWW.PLIIDEK.COM

These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System:

Pli-Dek System
ICC-ES ESR-2097

Detail:

FASCIA METAL TO GUTTER

Job:

Date: 05-3-2013

Dwn: H.K

Drawing Number:

PD-12