

Description:

The Pli-Dek PD WB Primer is a water based asphalt emulsion primer for use with hot-applied rubberized asphalt. It is a non-flammable, spray applied primer that improves the bond of the rubberized asphalt membrane to the concrete substrate.

Primary Use:

PD WB Primer is a water based asphalt emulsion primer used to promote adhesion of the hot-applied rubberized asphalt membrane waterproofing to the substrate.

Advantages:

- One component system
- Non-Flammable
- No VOC restrictions
- Low-Pressure spray application
- Can be installed at 40°F

Application:

PD WB Primer is applied onto the substrate to be waterproofed by a hand held sprayer prior to application of Pli-Dek Hot Rubber (HR).

Note: HR will not bond properly to wet primer.

Technical Information:

Asphalt by Weight	41%
(ASTM D 41)	
Density	8.3 lbs./gal
(ASTM D 449)	
Minimum Application	10°F (-12°C)
(ASTM D 5147)	

Product Cover Chart:

Approximate coverage rate of PD WB Primer is 200-400 sq. ft. per gallon.

Clean Up:

Use waterless hand cleaner for skin. Equipment and brushes may be cleaned up by using suitable solvents such as mineral spirits/methyl soyate. Care should be used in handling these solvents.

Warranty Information:

Contact Pli-Dek Systems, Inc. for specific warranty information.

Disclaimer:

This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek Systems, Inc. to be accurate. Pli-Dek Systems, Inc. does not assume any legal responsibility for use or reliance on the information supplied here.

