

**Description:**

The Pli-Dek Seam Paper is a 1½" wide, water resistant, reinforced, asphalt-laminated Kraft paper material that is used to cover plywood joints.

**Advantages:**

- High water vapor resistance
- Water resistance is 24 hours
- Reinforced with fiberglass scrim
- Resists tearing

**Color/Packaging:**

Brown in color. Available in a 1 ½" by 300 linear foot roll.

**Shelf Life/Storage:**

Protect from freezing. Do not store in direct sunlight.

**Application:**

*Surface Preparation:*

Ensure that the exterior plywood surface has been prepared in accordance with Pli-Dek Application Instructions. Ensure that all proper flashing is in place.

*Installation:*

Install PD Seam Tape centered over all joints/gaps in the wood deck substrate. Randomly staple the Seam Paper in place to provide temporary placement. The fastening pattern for the seam tape is @ 1½" O.C., the length of the seam tape, overlap seams and end laps @ 1½" O.C. the length of the seam and end lap.

**Limitations:**

Not recommended for below grade. Do not apply to frost covered surfaces, or below 13°C (55°F). Do not apply if rain is expected in 24 hours.

**Technical Data:**

Hazard warnings are not required for these products under OSHA hazard communication standard (29 CFR 1910.1200):

Natural Kraft Paper / Unsaturated Kraft Paper RATAN Asphalt Laminated Kraft – Grade B.

High melt point asphalt laminated between 2 sheets of BS 30 Kraft paper. Asphalt is low sulphur & virtually odor free.

Complies with Federal Specification UU-B-790A, Type I, Grade A, B & C, Style 4. Complies with UBC Standard 14-1.

**Disclaimer:**

*\*This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek Systems, Inc. to be accurate. Pli-Dek Systems, Inc. does not assume any legal responsibility for use or reliance on the information supplied here.*

