

PRODUCT INFORMATION SHEET GU80 STAMP MIX

Description:

The Pli-Dek GU80 Stamp Mix is a proprietary blend of various sands, that when combined with the GU80-1 Liquid Admixture and water, creates a polymer cementitious compound that can be used in the finish coat application as a stamped finish.

Uses:

The GU80 Stamp Mix is used to create a simulation of a stamped finish concrete application

Advantages:

- On-site Mixing
- 6,000 psi
- Up to 2% Grade
- Bonds to Existing Substrates
- Can be colored to any color
- Can be stained for a “modeled” look.
- Once cured, the PD Clear or GS13 can be applied to create a cleanable surface

Color/Packaging:

GU80-Stamp Mix is white in color is available in a 46 lbs. bag.

Shelf Life/Storage:

Transport and store in original, unopened, undamaged containers. Protect from freezing. Do not store in direct sunlight.

Clean Up:

Clean tools and hands with warm soapy water and rinse thoroughly.

Application Instructions:

A. General

1. There should always be of a ¼” per foot slope on the deck. The sloping is meant to divert water towards the scupper or drain. NOTE: DO NOT APPLY IN INCLEMENT WEATHER.

2. Air temperature for application of the Stamp Mix must be between 10°C (50° F) and 43°C (110°F) and must remain so for a minimum of 2-6 hours. 3. Do not allow foot traffic on the areas where the Stamp Mix was installed for a period of 24 hours.

**For Complete Application Instructions, please contact Pli-Dek Systems, Inc. **

Cure Time:

Allow 24 hours for drying, depending on weather condition. Cool temperatures or high humidity will slow the dry time

Limitations:

Air temperature for the application must be between 10°C (50°F) and 43°C (110°F) and must remain so for a minimum of 8 hours. Do not apply if rain is expected in 24 hours.

Warranty:

Please contact Pli-Dek LLC for details.

Disclaimer:

**This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek LLC to be accurate. Pli-Dek LLC does not assume any legal responsibility for use or reliance on the information supplied here.*

Technical Assistance:

Contact Pli-Dek LLC for any job specific questions.



Scan here to visit the Pli-Dek website