

PRODUCT INFORMATION SHEET GROUT TAPE

Application Instructions:

Application Instructions and coverage rates will vary based on intended use.



Description:

The Pli-Dek Grout Tape is an all-purpose fiberglass reinforced paper backed strapping tape with pressure-sensitive natural rubber/resin adhesive. Medium-tensile strength, high adhesion and medium-impact.

Uses:

- Pli-Dek System
- Con-Dek System
- PD Texture Coat

Advantages:

- Long Term Cost Effectiveness
- Added Protection
- Non Corrosive
- Decorative

Color/Packaging:

Color: Natural
 Roll Sizes: 3/4" x 60 yards
 3/8" x 60 yards
 1/2" x 60 yards
 1/4" x 60 yards
 Min. Order: 1 Roll

Storage:

Protect from freezing. Do not store container in direct sunlight.

Technical Data:

Backing	Medium Crepe Paper
Adhesive	Natural Rubber/Resin
Reinforcement	Fiberglass
Tensile Strength	198 lbs./in.
Elongation	4 % @ break
Total Thickness	9.8 mils
Operating Temperature Range	32° – 200° F

Limitations:

Not recommended for below grade. Do not apply to frost covered surfaces, or below 13°C (55°F). Do not apply if rain is expected in 24 hours and it must remain over 13°C (55°F) temperature for 24 hours.

Disclaimer:

**This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek LLC to be accurate. Pli-Dek LLC does not assume any legal responsibility for use or reliance on the information supplied here.*

Technical Assistance:

Contact Pli-Dek LLC for any job specific questions.



Scan here to visit the Pli-Dek website