

PRODUCT INFORMATION SHEET PD SEAM PAPER

Description:

The Pli-Dek Seam Paper is a 1½" wide, water resistant, reinforced, asphalt-laminated Kraft paper material that is used to cover plywood joints.

Advantages:

- High water vapor resistance
- Water resistance is 24 hours
- Reinforced with fiberglass scrim
- Resists tearing

Color/Packaging:

Brown in color. Available in a 1 ½" by 300 linear foot roll.

Shelf Life/Storage:

Protect from freezing. Do not store in direct sunlight.

Application:

Surface Preparation:

Ensure that the exterior plywood surface has been prepared in accordance with Pli-Dek Application Instructions. Ensure that all proper flashing is in place.

Installation:

Install PD Seam Tape centered over all joints/gaps in the wood deck substrate. Randomly staple the Seam Paper in place to provide temporary placement. The fastening pattern for the seam tape is @ 1½" O.C., the length of the seam tape, overlap seams and end laps @ 1½" O.C. the length of the seam and end lap.

Limitations:

Not recommended for below grade. Do not apply to frost covered surfaces, or below 13°C (55°F). Do not apply if rain is expected in 24 hours.

Technical Data:

Hazard warnings are not required for these products under osha hazard communication standard (29 CFR 1910.1200):

Natural Kraft Paper / Unsaturated Kraft Paper RATAN Asphalt Laminated Kraft – Grade B.

High melt point asphalt laminated between 2 sheets of BS 30 Kraft paper. Asphalt is low sulphur & virtually odor free.

Complies with Federal Specification UU-B-790A, Type I, Grade A, B & C, Style 4. Complies with UBC Standard 14-1.

Disclaimer:

**This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek LLC to be accurate. Pli-Dek LLC does not assume any legal responsibility for use or reliance on the information supplied here.*

Technical Assistance:

Contact Pli-Dek LLC for any job specific questions.



Scan here to visit the Pli-Dek website