



PD Stain Color Vial Black

ICP Building Solutions Group/Pli-Dek

Version No: 2.3.6.8
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 07/30/2021
Print Date: 07/30/2021
S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	PD Stain Color Vial Black
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Color
--------------------------	-------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group/Pli-Dek
Address	4565 W. Watkins Street Phoenix AZ 85043 United States
Telephone	623-435-2277
Fax	Not Available
Website	www.ICPGROUP.com
Email	sds@icpgroup.com

Emergency phone number

Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Skin Sensitizer Category 1
----------------	----------------------------

Label elements

Hazard pictogram(s)	
---------------------	--

Signal word	Warning
-------------	---------

Hazard statement(s)

H317	May cause an allergic skin reaction.
------	--------------------------------------

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

PD Stain Color Vial Black

P202	Do not handle until all Safety Precautions have been read and understood.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P272	Contaminated work clothing should not be allowed out of the workplace.
P261	Avoid breathing mist/vapours/spray.

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	IF SKIN irritation occurs; get medical advice/attention.
P363	Wash contaminated clothing before reuse.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
14807-96-6	15-40	<u>talc</u>
1333-86-4	1-10	<u>carbon black</u>
55406-53-6	0.1-1.5	<u>3-iodo-2-propynyl butyl carbamate</u>
14808-60-7	0.1-1	<u>silica crystalline - quartz</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	<p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with water. ▶ If irritation continues, seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Special protective equipment and precautions for fire-fighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course.
----------------------	--

Continued...

PD Stain Color Vial Black

Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: carbon dioxide (CO ₂) hydrogen iodide silicon dioxide (SiO ₂) other pyrolysis products typical of burning organic material. May emit corrosive fumes.
------------------------------	---

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes.
Major Spills	Moderate hazard. <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ DO NOT allow clothing wet with material to stay in contact with skin
Other information	Store in the dark. <ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Metal can or drum ▶ Packaging as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	talc	Silicates (less than 1% crystalline silica): Talc (not containing asbestos)	20 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	talc	Silicates (less than 1% crystalline silica): Talc (containing asbestos)	Not Available	Not Available	Not Available	Use asbestos limit
US OSHA Permissible Exposure Limits (PELs) Table Z-3	talc	Silicates (less than 1% crystalline silica): Soapstone	20 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	talc	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m ³	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	talc	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m ³	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	talc	Talc (containing no asbestos and less than 1% quartz) - respirable	2 mg/m ³	Not Available	Not Available	Not Available

Continued...

PD Stain Color Vial Black


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US ACGIH Threshold Limit Values (TLV)	talc	Talc: Containing asbestos fibers	Not Available	Not Available	Not Available	A1
US ACGIH Threshold Limit Values (TLV)	talc	Talc: Containing no asbestos fibers (Respirable particulate matter)	2 mg/m3	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	carbon black	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Ca; TWA 0.1 mg PAHs/m3 [Carbon black in presence of polycyclic aromatic hydrocarbons (PAHs)] See Appendix A See Appendix C
US ACGIH Threshold Limit Values (TLV)	carbon black	Carbon black (Inhalable particulate matter)	3 mg/m3	Not Available	Not Available	A3
US OSHA Permissible Exposure Limits (PELs) Table Z-3	3-iodo-2-propynyl butyl carbamate	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	3-iodo-2-propynyl butyl carbamate	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	3-iodo-2-propynyl butyl carbamate	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	3-iodo-2-propynyl butyl carbamate	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	3-iodo-2-propynyl butyl carbamate	Particulates not otherwise regulated	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	silica crystalline - quartz	Silica, crystalline - α -quartz and cristobalite (Respirable particulate matter)	0.025 mg/m3	Not Available	Not Available	A2

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
carbon black	9 mg/m3	99 mg/m3	590 mg/m3
3-iodo-2-propynyl butyl carbamate	3.3 mg/m3	36 mg/m3	220 mg/m3
silica crystalline - quartz	0.075 mg/m3	33 mg/m3	200 mg/m3

Ingredient	Original IDLH	Revised IDLH
talc	1,000 mg/m3	Not Available
carbon black	1,750 mg/m3	Not Available
3-iodo-2-propynyl butyl carbamate	Not Available	Not Available
silica crystalline - quartz	25 mg/m3 / 50 mg/m3	Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▸ Safety glasses with side shields. ▸ Chemical goggles. ▸ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below

PD Stain Color Vial Black

Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>NOTE:</p> <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C apron. ▶ Barrier cream.

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Light sensitive.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

PD Stain Color Vial Black

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of dusts, generated by the material, during the course of normal handling, may be harmful.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

PD Stain Color Vial Black	<table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">TOXICITY</th> <th style="text-align: left;">IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available						
TOXICITY	IRRITATION										
Not Available	Not Available										
talc	<table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">TOXICITY</th> <th style="text-align: left;">IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: >2000 mg/kg^[1]</td> <td>Eye: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td>Inhalation(Rat) LC50; >2.1 mg/l4h^[1]</td> <td>Skin (human): 0.3 mg/3d-I mild</td> </tr> <tr> <td>Oral(Rat) LD50; >5000 mg/kg^[1]</td> <td>Skin: no adverse effect observed (not irritating)^[1]</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Inhalation(Rat) LC50; >2.1 mg/l4h ^[1]	Skin (human): 0.3 mg/3d-I mild	Oral(Rat) LD50; >5000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]		
TOXICITY	IRRITATION										
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]										
Inhalation(Rat) LC50; >2.1 mg/l4h ^[1]	Skin (human): 0.3 mg/3d-I mild										
Oral(Rat) LD50; >5000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]										
carbon black	<table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">TOXICITY</th> <th style="text-align: left;">IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: >2000 mg/kg^[1]</td> <td>Eye: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td>Oral(Rat) LD50; >8000 mg/kg^[1]</td> <td>Skin: no adverse effect observed (not irritating)^[1]</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	Oral(Rat) LD50; >8000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]				
TOXICITY	IRRITATION										
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]										
Oral(Rat) LD50; >8000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]										
3-iodo-2-propynyl butyl carbamate	<table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">TOXICITY</th> <th style="text-align: left;">IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Dermal (rabbit) LD50: >2000 mg/kg^[1]</td> <td>Eye: adverse effect observed (irreversible damage)^[1]</td> </tr> <tr> <td>Inhalation(Rat) LC50; 0.63 mg/l4h^[1]</td> <td>Eye: Irritating</td> </tr> <tr> <td>Oral(Rat) LD50; 1056 mg/kg^[1]</td> <td>Skin: no adverse effect observed (not irritating)^[1]</td> </tr> <tr> <td></td> <td>Skin: Slight irritant</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]	Inhalation(Rat) LC50; 0.63 mg/l4h ^[1]	Eye: Irritating	Oral(Rat) LD50; 1056 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]		Skin: Slight irritant
TOXICITY	IRRITATION										
Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]										
Inhalation(Rat) LC50; 0.63 mg/l4h ^[1]	Eye: Irritating										
Oral(Rat) LD50; 1056 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]										
	Skin: Slight irritant										
silica crystalline - quartz	<table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: left;">TOXICITY</th> <th style="text-align: left;">IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Oral(Rat) LD50; 500 mg/kg^[2]</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Oral(Rat) LD50; 500 mg/kg ^[2]	Not Available						
TOXICITY	IRRITATION										
Oral(Rat) LD50; 500 mg/kg ^[2]	Not Available										
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances										

PD Stain Color Vial Black	Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.
TALC	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. The overuse of talc in nursing infants has resulted in respiratory damage causing fluid in the lungs and lung inflammation which may lead to death within hours of inhalation. Long-term exposure can also cause a variety of respiratory symptoms. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
CARBON BLACK	Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.
3-iodo-2-propynyl butyl carbamate	Carbamate pesticides are less dangerous than organophosphorus pesticides. It requires higher dose to produce toxicity or mortality. However, its toxicity via skin contact is low to moderate. For 3-iodo-2-propynyl butyl carbamate (IPBC): Acute toxicity studies with IPBC show low toxicity except severe eye irritation. Animal testing showed that extended exposure may cause

PD Stain Color Vial Black

	decreased weight gain and increased red cell and eosinophil counts. One study showed the possibility of increased breast cancer on extended contact. IPBC may cause defects in bone development at very high levels.
SILICA CRYSTALLINE - QUARTZ	WARNING: For inhalation exposure <u>ONLY</u> : This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 µm) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung disease. Intermittent exposure produces; focal fibrosis, (pneumoconiosis), cough, dyspnoea, liver tumours. * Millions of particles per cubic foot (based on impinger samples counted by light field techniques). NOTE : the physical nature of quartz in the product determines whether it is likely to present a chronic health problem.
PD Stain Color Vial Black & 3-IODO-2-PROPYNYL BUTYL CARBAMATE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.
TALC & CARBON BLACK	No significant acute toxicological data identified in literature search.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

PD Stain Color Vial Black	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
talc	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	89581.016mg/l	2
	NOEC(ECx)	720h	Algae or other aquatic plants	918.089mg/l	2
	EC50	96h	Algae or other aquatic plants	7202.7mg/l	2
carbon black	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>0.2mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	33.076-41.968mg/l	4
	NOEC(ECx)	24h	Crustacea	3200mg/l	1
3-iodo-2-propynyl butyl carbamate	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	840h	Fish	0.013mg/L	4
	LC50	96h	Fish	0.077-0.124mg/L	4
	EC50	48h	Crustacea	0.04mg/L	5
silica crystalline - quartz	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
3-iodo-2-propynyl butyl carbamate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
3-iodo-2-propynyl butyl	LOW (LogKOW = 2.4542)

Continued...

PD Stain Color Vial Black

Ingredient	Bioaccumulation
carbamate	

Mobility in soil

Ingredient	Mobility
3-iodo-2-propynyl butyl carbamate	LOW (KOC = 365.3)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	
	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Authority for disposal. ▶ Bury or incinerate residue at an approved site.

SECTION 14 Transport information

Labels Required

Marine Pollutant	
	NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
talc	Not Available
carbon black	Not Available
3-iodo-2-propynyl butyl carbamate	Not Available
silica crystalline - quartz	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
talc	Not Available
carbon black	Not Available
3-iodo-2-propynyl butyl carbamate	Not Available
silica crystalline - quartz	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

talc is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
US ACGIH Threshold Limit Values (TLV)
US ACGIH Threshold Limit Values (TLV) - Carcinogens
US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)
US OSHA Permissible Exposure Limits (PELs) Table Z-1
US OSHA Permissible Exposure Limits (PELs) Table Z-3
US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
US TSCA Chemical Substance Inventory - Interim List of Active Substances

carbon black is found on the following regulatory lists

PD Stain Color Vial Black

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

3-iodo-2-propynyl butyl carbamate is found on the following regulatory lists

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPCRA Section 313 Chemical List

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

silica crystalline - quartz is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

US - California Proposition 65 - Carcinogens

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US ACGIH Threshold Limit Values (TLV)

US ACGIH Threshold Limit Values (TLV) - Carcinogens

US DOE Temporary Emergency Exposure Limits (TEELs)

US National Toxicology Program (NTP) 14th Report Part A Known to be Human Carcinogens

US NIOSH Carcinogen List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Carcinogens Listing

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - California Proposition 65 - Carcinogens: Listed substance

carbon black, silica crystalline - quartz

Continued...

PD Stain Color Vial Black

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (talc; carbon black; 3-iodo-2-propynyl butyl carbamate; silica crystalline - quartz)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	07/30/2021
Initial Date	04/21/2020

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
1.3.6.8	07/30/2021	Chronic Health, Classification, Ingredients, Personal Protection (Respirator), Storage (storage requirement)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index
 AIIC: Australian Inventory of Industrial Chemicals
 DSL: Domestic Substances List
 NDSL: Non-Domestic Substances List
 IECSC: Inventory of Existing Chemical Substance in China
 EINECS: European INventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
 NLP: No-Longer Polymers
 ENCS: Existing and New Chemical Substances Inventory
 KECI: Korea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 TSCA: Toxic Substances Control Act
 TCSI: Taiwan Chemical Substance Inventory
 INSQ: Inventario Nacional de Sustancias Químicas
 NCI: National Chemical Inventory
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.