



NOTES:

- CONSIDERATION MUST BE MADE IN REGARDS TO THE HEIGHT OF THE SHEET METAL FLASHING AT THE WALL TO DECK JUNCTION IN ORDER TO ALLOW THE EXTENSION OF THE METAL TO 4" BEYOND THE FINISHED DECK SURFACE ALLOWING 2" OF WORK SPACE.
- WHEN USING IN CONJUNCTION WITH CON-DEK SYSTEM, APPLY SLOPE MATERIAL PRIOR TO INSTALLATION OF FIBERGLASS AND PD RESIN (2 COATS).
- CRICKET LOCATION VARIES ACCORDING TO DRAIN/SCUPPER LOCATIONS.
- REFER TO CON-DEK APPLICATION INSTRUCTION AND SPECIFICATIONS FOR INSTALLATION GUIDELINES.

DETAIL-ENCLOSED DECK LOW WALL DRAINS & SCUPPER-CONCRETE
SUBSTRATE

SCALE: N.T.S.



These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System:		Con-Dek System by Pli-Dek Systems, Inc. ICC-ES ESR-2097	
Detail:		ENCLOSED DECK LOW WALL DRAINS & SCUPPER CONCRETE SUBSTRATE	
Job:		Drawing Number:	
Date:	11/01/2020	CD-10	
Dwn:	E.L.		