

LIGHT WEIGHT/HARDROCK
CONCRETE SLOPING 1/8"
PER FOOT MIN.

ATTACHMENT OF T-BAR
TO BE SEALED WITH ASTM-C-920
POLYURETHANE SEALANT

SELF ADHESIVE
MEMBRANE SPACER
2" W x 36" O.C
(2" HORIZONTAL,
1" VERTICAL)

MIN. 26 GAUGE
GALVANIZED SHEET
METAL FLASHING
(3/16" RISE)
(BONDERIZED)

VERTICAL FLASHING
COATED WITH PD
FLASH COAT AND/OR
GS88 PIGMENTED
SEALER REFER TO
TB-110 FOR INCLEMENT
WEATHER

T-BAR
CONCRETE STOP

STUCCO FINISH
(BY OTHERS)

BUILDING PAPER

GU80 TOP COAT

3/4 OZ. FIBERGLASS & PD RESIN

GU80 BASE COAT

2.5 GALVANIZED METAL LATH

SLOPED DECK

5/8" MIN. EXPOSURE 1 SHEATHING
(3/4" RECOMMENDED) SLOPE 1/4"
PER 12"

NAILER OR EXTEND
PLYWOOD
OVER EXTERIOR FINISH

STRUCTURAL DESIGN
(BY OTHERS)

1/2" DRIP

DETAIL- T-BAR METAL DETAIL

SCALE: N.T.S



These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System: Pli-Dek System
ICC-ES ESR-2097
Detail: T-BAR METAL DETAIL

Job: _____
Date: 11/01/2020
Dwn: E.L.

Drawing Number:
PD-15