

FACE NAIL (A MIN. OF TWO NAILS PER SIDE) AT THE FLASHING ON EACH SIDE OF POST

FLASHING IS SECURED TO SUBFLOOR WITH NAILS ON ALL SIDES

26 GAUGE GALVANIZED, FLAT METAL INSTALLED ON ALL CORNERS OF THE POST AND NAILED TO THE SUBSTRATE AND SEAL WITH SEALANT

WOOD POST

ASTM C-920 POLYURETHANE SEALANT.

1" x 4" NOTCHED WOOD TRIM AROUND PERIMETER OF BASE (OPTIONAL)

6"

2"

5/8" MIN. EXPOSURE
1 SHEATHING
(3/4" RECOMMENDED)
SLOPE 1/4" PER 12"

STRUCTURAL DESIGN
(BY OTHERS)

1/8" OR 1/4" KERF CUT AROUND POST

WOOD POST

APPLY ASTM C-920 POLYURETHANE SEALANT BEHIND FLASHING AND AT THE TOP OF THE FLASHING

APPLY ASTM C-920 POLYURETHANE SEALANT AFTER COMPLETION OF THE Pli-DEK BASE COAT AROUND BASE OF POST.

Pli-DEK SYSTEM TERMINATES AT THIS POINT. GS88 TO BE COATED ON ALL VERTICAL FLASHING

ASTM C-920 SEALANT

GS88 PIGMENTED SEALER

GU80 TOP COAT

3/4 OZ. FIBERGLASS & PD RESIN (CONTACT Pli-DEK FOR REQUIREMENTS)

GU80 BASE COAT

2.5 GALVANIZED METAL LATH

SLOPED DECK

26 GAUGE (BONDERIZED) 2-PIECE SHEET METAL SADDLE MIN. 4" LAP FULLY BEDDED IN SEALANT. (ALL 4 SIDES OF POST TO BE FLASHED)

POST CONNECTION
(BY OTHERS)

DETAIL-WOOD POST FLASHING

SCALE: N.T.S.



These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System: Pli-Dek System
ICC-ES ESR-2097
Detail: WOOD POST FLASHING

Job: _____
Date: 11/01/2020
Dwn: E.L.

Drawing Number:
PD-19A