



NOTES:

- CONSIDERATION MUST BE MADE IN REGARDS TO THE HEIGHT OF THE SHEET METAL FLASHING AT THE WALL TO DECK JUNCTION IN ORDER TO ALLOW THE SLOPING MIX TO REMAIN A MINIMUM OF 2" BELOW THE FINISHED WELL SYSTEM.
- THE PLI-DEK SYSTEM IS INSTALLED UP TO THE BASE COAT STAGE PRIOR TO INSTALLATION OF SLOPING MATERIAL.
- WHEN USING IN CONJUNCTION WITH PLI-DEK SYSTEM, APPLY SLOPE MATERIAL PRIOR TO INSTALLATION OF FIBERGLASS AND PD RESIN.
- CRICKET LOCATION VARIES ACCORDING TO DRAIN/SCUPPER LOCATIONS.
- REFER TO PLI-DEK APPLICATION INSTRUCTION AND SPECIFICATIONS FOR INSTALLATION GUIDELINES.

DETAIL-ENCLOSED DECK DRAINAGE CRICKET-INCLEMENT WEATHER
SCALE: N.T.S.



These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System:		Pli-Dek System ICC-ES ESR-2097	
Detail:		ENCLOSED DECK LOW WALL DRAINAGE CRICKET INCLEMENT WEATHER	
Job:		Drawing Number:	
Date:	11/01/2020	PD-21-IW	
Dwn:	E.L.		