

2"x 6", 26 GAUGE
GALVANIZED
"L" METAL
(BONDERIZED)

SIDING
(BY OTHERS)

BUILDING PAPER

150 MM
(6") MIN.

50 MM
(2") MIN.

VERTICAL FLASHING
CAN BE COATED WITH 3/4 OZ.
FIBERGLASS & PD RESIN OR PD
FLASH COAT AND FLASH COAT
SEAM TAPE OR SELF-ADHERING
DRYWALL MESH TAPE REFER TO
TB-110 FOR INCLEMENT WEATHER

GS88 PIGMENTED SEALER
GU80 TOP COAT
3/4 OZ FIBERGLASS & PD RESIN
(CONTACT PLI-DEK FOR
REQUIREMENTS)
GU80 BASE COAT
2.5 GALVANIZED
METAL LATH

SLOPED DECK

50MM
(2") MIN.

5/8" MIN. EXPOSURE 1 SHEATHING
(3/4" RECOMMENDED)
SLOPE 1/4" PER 12"

DETAIL-DECK TO WALL FLASHING-SIDING

SCALE: N.T.S.



PLI-DEK
WATERPROOFING SOLUTIONS
150 Dascomb Rd., Andover, MA 01810
Phone: 800.364.0287 * Fax: 951.834.9555
WWW.PLI-DEK.COM

These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System:		Pli-Dek System ICC-ES ESR-2097	
Detail:		DECK TO WALL FLASHING-SIDING	
Job:		Drawing Number:	
Date:	11/01/2020	PD-8	
Dwn:	E.L.		