

PRODUCT INFORMATION SHEET SLOPE MIX-DP

Description:

The Pli-Dek Slope Mix - DP is a proprietary blend of various sands, that when mixed with water, creates an auxiliary sloping compound.

Uses:

Slope Mix-DP is used as an auxiliary sloping compound to slope up to 2% grade.

Advantages:

- On-site Mixing
- 6,000 psi
- Bonds to Existing Substrates
- Sloping to Facilitate Water Movement

Color/Packaging:

Slope Mix-DP Coat is gray in color and available in 50 lb. bags.

Shelf Life/Storage:

Transport and store in original, unopened, undamaged containers. Protect from freezing. Do not store in direct sunlight.

Clean Up:

Clean tools and hands with warm soapy water and rinse thoroughly.

Mixing Instructions:

Pour 1.2 gallons of water into a clean 19L (5 gallon) plastic container.

Add one 50lbs. bag/pail of Pli-Dek Slope Mix-DP powder. Mix thoroughly for 3 to 4 minutes, with a Wind-lock B-M1 mixing blade, or equivalent, powered by a 13mm (1/2 inch) variable speed drill, capable of producing 1000 RPMs.

Application Instructions:

A. General

1. Pli-Dek recommend 1/4" per foot of slope on the deck. The sloping is meant to divert water towards the scupper or drain. **NOTE: DO NOT APPLY IN INCLEMENT WEATHER.**
2. Air temperature for application of Slope Mix-DP must be between 10°C (50°F) and 43°C (110°F) and must remain so for a minimum of 2-6 hours.
3. Do not allow foot traffic on the areas where the slope mix was installed until for a period of 24 hours.
4. Do not allow foot traffic on the areas where the slope mix was installed until for a period of 24 hours.

****For complete sloping instructions, contact Pli-Dek LLC****

Cure Time:

Allow 24 hours for drying, depending on weather condition. Cool temperatures or high humidity will slow the dry time.

Limitations:

Do not apply to frost covered surfaces, or below 13°C (55°F). Do not apply if rain is expected in 24 hours. Do not apply under foggy conditions. Apply on warm, sunny days.

Warranty:

Please contact Pli-Dek LLC for details.

Disclaimer:

**This information is furnished without warranty, representation, inducement or license of any kind, except sources believed by Pli-Dek LLC to be accurate. Pli-Dek LLC does not assume any legal responsibility for use or reliance on the information supplied here.*

Technical Assistance:

Contact Pli-Dek LLC for any job specific questions.



Scan here to visit the Pli-Dek website