

MIN. 2" x 6", 26 GAUGE
PAN FLASHING
GALVANIZED
(BONDERIZED)

MIN. 2" x 6", 26 GA.
GALVANIZED "L" METAL
(BONDERIZED)
ASTM C-920
POLYURETHANE SEALANT

EXPANSION MATERIAL
BETWEEN FLASHING
AND SURFACING
(BY OTHERS)

PAN FLASHING
(EMBED PAN FLASHING
IN FULL BED OF ASTM C-920
POLYURETHANE SEALANT)

SURFACING
(BY OTHERS)

PD DRAIN BOARD
(AS SPECIFIED)

PROTECTION COURSE

HD-250 BY PLI-DEK SYSTEM, INC.
(PER SPECIFIED MIL
THICKNESS CR, HR, OR PMA)

GU80 BASE COAT

SLOPED DECK

2.5 GALVANIZED METAL
LATH

5/8" MIN. EXPOSURE 1 SHEATHING
(3/4" RECOMMENDED). SLOPE
1/4" PER 12"

DETAIL-THRESHOLD FLASHING DETAIL

SCALE: N.T.S.



41610 Date St., Suite 104 * Murrieta, CA. 92562
Phone: 800.364.0287 * Fax: 951.834.9555
WWW.PLIIDEK.COM

These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

HD-250 by Pli-Dek System, Inc.

THRESHOLD FLASHING DETAIL

Job:		Drawing Number: HD-1
Date:	09-1-2013	
Dwn:	H.K	