

2"x 6", 26 GAUGE  
GALVANIZED  
"L" METAL

BUILDING PAPER  
SIDING  
(BY OTHERS)

150 MM  
(6") MIN.

50 MM  
(2") MIN.

ASTM C-920 POLYURETHANE  
SEALANT

VERTICAL FLASHING SHALL BE  
COATED WITH 3/4 OZ. FIBERGLASS  
AND PD RESIN OR PD FLASH COAT  
AND FLASH COAT SEAM TAPE OR  
SELF-ADHERING DRYWALL MESH  
TAPE

GS88 PIGMENTED SEALER

GU80 TOP COAT

3/4 OZ. FIBERGLASS & PD RESIN

GU80 BASE COAT

2.5 G90 GALVANIZED METAL  
LATH

SLOPED DECK

50MM  
(2") MIN.

5/8" MIN. EXPOSURE 1 SHEATHING  
(3/4 " RECOMMENDED)  
SLOPE 1/4" PER 12"

**DETAIL-DECK TO WALL FLASHING-SIDING-INCLEMENT WEATHER**  
SCALE: N.T.S.



**PLI-DEK**  
WATERPROOFING SOLUTIONS  
41610 Date St., Suite 104 \* Murrieta, CA. 92562  
Phone: 800.364.0287 \* Fax: 951.834.9555  
WWW.PLI-DEK.COM

These waterproofing procedures are not to be used for permit and should be reviewed by the project architect. The waterproofing procedures are not complete plans or specifications and a professional design professional should be contacted prior to performing major waterproofing and repairs.

System:		Pli-Dek System ICC-ES ESR-2097	
Detail:		DECK TO WALL FLASHING-SIDING INCLEMENT WEATHER	
Job:		Drawing Number:	
Date:	04/01/2019	PD-8-IW	
Dwn:	E.L.		