

PD Stain Color Vial Terra Cotta

ICP Building Solutions Group/Pli-Dek

Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **04/22/2020** Print Date: **04/22/2020** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	PD Stain Color Vial Terra Cotta
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses colo

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group/Pli-Dek
Address	4565 W. Watkins Street Phoenix AZ Not applicable
Telephone	623-435-2277
Fax	Not Available
Website	www.ICPGROUP.com
Email	Not Available

Emergency phone number

goc, pccc.	
Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Skin Sensitizer Category 1

Label elements

Hazard pictogram(s)



SIGNAL WORD

WARNING

Hazard statement(s)

H317 May cause an allergic skin reaction.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

Version No: 1.1 Page 2 of 9 Issue Date: 04/22/2020

PD Stain Color Vial Terra Cotta

Print Date: 04/22/2020

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	

Precautionary statement(s) Prevention

P202	Do not handle until all Safety Precautions have been read and understood.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P261	Avoid breathing mist/vapours/spray.		

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.	
P333+P313	IF SKIN irritation or rash occurs: get medical advice/attention	
P363	Wash contaminated clothing before reuse.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
14807-96-6	1-10	<u>talc</u>
1309-37-1	1-5	ferric oxide
1317-34-6	.5-5	manganese sesquioxide

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short term repeated exposures to iron and its derivatives:

- Always treat symptoms rather than history.
- In general, however, toxic doses exceed 20 mg/kg of ingested material (as elemental iron) with lethal doses exceeding 180 mg/kg.
- Control of iron stores depend on variation in absorption rather than excretion. Absorption occurs through aspiration, ingestion and burned skin.
- Hepatic damage may progress to failure with hypoprothrombinaemia and hypoglycaemia. Hepatorenal syndrome may occur.
- Iron intoxication may also result in decreased cardiac output and increased cardiac pooling which subsequently produces hypotension.
- Serum iron should be analysed in symptomatic patients. Serum iron levels (2-4 hrs post-ingestion) greater that 100 ug/dL indicate poisoning with levels, in excess of 350 ug/dL, being potentially serious. Emesis or lavage (for obtunded patients with no gag reflex) are the usual means of decontamination.
- Activated charcoal does not effectively bind iron.
- ▶ Catharsis (using sodium sulfate or magnesium sulfate) may only be used if the patient already has diarrhoea.

Version No: 1.1 Page 3 of 9 Issue Date: 04/22/2020 Print Date: 04/22/2020

PD Stain Color Vial Terra Cotta

▶ Deferoxamine is a specific chelator of ferric (3+) iron and is currently the antidote of choice. It should be administered parenterally. [Ellenhorn and Barceloux: Medical Toxicology]

Both dermal and oral toxicity of manganese salts is low because of limited solubility of manganese. No known permanent pulmonary sequelae develop after acute manganese exposure. Treatment is supportive.

[Ellenhorn and Barceloux: Medical Toxicology]

In clinical trials with miners exposed to manganese-containing dusts, L-dopa relieved extrapyramidal symptoms of both hypo kinetic and dystonic patients. For short periods of time symptoms could also be controlled with scopolamine and amphetamine. BAL and calcium EDTA prove ineffective.

[Gosselin et al: Clinical Toxicology of Commercial Products.]

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Special protective equipment a	and precautions for fire-fighters
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire.
Fire/Explosion Hazard	Under certain conditions the material may become combustible because of the ease of ignition which occurs after the material reaches a high specific area ratio (thin sections, fine particles, or molten states). However, the same material in massive solid form is comparatively difficult to ignite. Decomposition may produce toxic fumes of: silicon dioxide (SiO2) metal oxides. May emit poisonous fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

May emit corrosive fumes.

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.
Major Spills	 Absorb or contain isothiazolinone liquid spills with sand, earth, inert material or vermiculite. The absorbent (and surface soil to a depth sufficient to remove all of the biocide) should be shovelled into a drum and treated with an 11% solution of sodium metabisulfite (Na2S2O5) or sodium bisulfite (NaHSO3), or 12% sodium sulfite (Na2SO3) and 8% hydrochloric acid (HCI).

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling ▶ Avoid all personal contact, including inhalation. Safe handling ▶ Wear protective clothing when risk of exposure occurs. ► DO NOT allow clothing wet with material to stay in contact with skin Other information Conditions for safe storage, including any incompatibilities Polyethylene or polypropylene container. Suitable container Packing as recommended by manufacturer.

▶ WARNING: Avoid or control reaction with peroxides. All *transition meta*l peroxides should be considered as potentially explosive.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Derivative of electropositive metal.

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Storage incompatibility

INGREDIENT DATA

Version No: 1.1 Page 4 of 9 Issue Date: 04/22/2020 Print Date: 04/22/2020

PD Stain Color Vial Terra Cotta

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	talc	Hydrous magnesium silicate, Steatite talc	2 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	talc	Massive talc, Soapstone silicate, Steatite	6 (total), 3 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Talc	Not Available	Not Available	Not Available	(Name ((less than 1% crystalline silica); (containing asbestos) Use asbestos limit))
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Talc	20 mppcf	Not Available	Not Available	(Name ((less than 1% crystalline silica); (not containing asbestos))); (TWA mppcf (((c) Containing less than 1% quartz; if 1% quartz or more, use quartz limit.)))
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Soapstone	20 mppcf	Not Available	Not Available	(Name ((less than 1% crystalline silica)))
US OSHA Permissible Exposure Levels (PELs) - Table Z1	talc	Silicates (less than 1% crystalline silica): Talc (containing asbestos); use asbestos limit	Not Available	Not Available	Not Available	see 29 CFR 1910.1001; See Table Z-3
US OSHA Permissible Exposure Levels (PELs) - Table Z1	talc	Silicates (less than 1% crystalline silica): Talc (containing no asbestos), respirable dust	Not Available	Not Available	Not Available	See Table Z-3
US ACGIH Threshold Limit Values (TLV)	talc	Talc: Containing asbestos fibers	Not Available	Not Available	Not Available	Use Asbestos TLV® (K)
US ACGIH Threshold Limit Values (TLV)	talc	Talc: Containing no asbestos fibers	2 mg/m3	Not Available	Not Available	Pulm fibrosis; pulm func
US NIOSH Recommended Exposure Limits (RELs)	ferric oxide	Ferric oxide, Iron(III) oxide	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	ferric oxide	Iron(III)oxide, Iron oxide red, Red iron oxide, Red oxide	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ferric oxide	Rouge: Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ferric oxide	Iron oxide fume	10 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ferric oxide	Rouge: Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ferric oxide	Iron oxide (Fe2O3) (Inhalable fraction and vapor)	5 mg/m3	Not Available	Not Available	Pneumoconiosis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	manganese sesquioxide	Manganese compounds (as Mn)	Not Available	Not Available	5 mg/m3	Not Available
US ACGIH Threshold Limit Values (TLV)	manganese sesquioxide	Manganese, elemental and inorganic compounds, as Mn (Inhalable particulate matter)	0.1 mg/m3	Not Available	Not Available	CNS impair
US ACGIH Threshold Limit Values (TLV)	manganese sesquioxide	Manganese, elemental and inorganic compounds, as Mn (Inhalable fraction and	0.02 mg/m3	Not Available	Not Available	CNS impair

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ferric oxide	Iron oxide; (Ferric oxide)	15 mg/m3	360 mg/m3	2,200 mg/m3
manganese sesquioxide	Manganese(III) oxide	4.3 mg/m3	7.2 mg/m3	43 mg/m3

Ingredient	Original IDLH	Revised IDLH
talc	1,000 mg/m3	Not Available
ferric oxide	2,500 mg/m3	Not Available
manganese sesquioxide	500 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Personal protection





vapor)





Eye and face protection

- ► Safety glasses with side shields.
- ► Chemical goggles.

Skin protection See Hand protection below

Version No: **1.1** Page **5** of **9** Issue Date: **04/22/2020**

PD Stain Color Vial Terra Cotta

Print Date: 04/22/2020

Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Butyl rubber gloves Nitrile rubber gloves (Note: Nitric acid penetrates nitrile gloves in a few minutes.)
Body protection	See Other protection below
Other protection	► Overalls. ► P.V.C.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Light sensitive.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Manganese fume is toxic and produces nervous system effects characterised by tiredness. Acute poisoning is rare although acute inflammation of the lungs may occur.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual. Taken by mouth, isothiazolinones have moderate to high toxicity. The major signs of toxicity are severe stomach irritation, lethargy, and inco-ordination. Poisonings rarely occur after oral administration of manganese salts because they are poorly absorbed from the gut.

Version No: 1.1 Page 6 of 9 Issue Date: 04/22/2020

PD Stain Color Vial Terra Cotta

Print Date: 04/22/2020

Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Solutions of isothiazolinones may be irritating or even damaging to the skin, depending on concentration. A concentration of over 0.1% can irritate, and over 0.5% can cause severe irritation. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Solutions containing isothiazolinones may damage the mucous membranes and cornea. Animal testing showed very low concentrations (under 0.1%) did not cause irritation, while higher levels (3-5.5%) produced severe irritation and damage to the eye.			
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Manganese is an essential trace element. Chronic exposure to low levels of manganese can include a mask-like facial expression, spastic gait, tremors, slurred speech, disordered muscle tone, fatigue, anorexia, loss of strength and energy, apathy and poor concentration. Chronic excessive intake of iron have been associated with damage to the liver and pancreas. People with a genetic disposition to poor control over iron are at an increased risk. The isothiazolinones are known contact sensitisers. Sensitisation is more likely with the chlorinated species as opposed to the non-chlorinated species. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.			
	TOXICITY	IRRITATION		
PD Stain Color Vial Terra Cotta	Not Available	Not Available		
	TOXICITY	IRRITATION		
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse	effect observed (not irritating) ^[1]	
talc	Oral (rat) LD50: >5000 mg/kg ^[1]	Skin (human): 0.	3 mg/3d-l mild	
		Skin: no adverse	effect observed (not irritating) ^[1]	
	TOXICITY			
ferric oxide	Oral (rat) LD50: >10000 mg/kg ^[2]	Not Available		
	TOXICITY	IRRITATION		
manganese sesquioxide	Oral (rat) LD50: >2000 mg/kg ^[1]	Eye: no adverse	effect observed (not irritating) ^[1]	
	Skin: no adverse effect observed (not irri		effect observed (not irritating) ^[1]	
Legend:	Nalue obtained from Europe ECHA Registered Substance specified data extracted from RTECS - Register of Toxic	•	ined from manufacturer's SDS. Unless otherwise	
PD Stain Color Vial Terra Cotta	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.			
TALC	No significant acute toxicological data identified in literature search. The overuse of talc in nursing infants has resulted in respiratory damage causing fluid in the lungs and lung inflammation which may lead to death within hours of inhalation. Long-term exposure can also cause a variety of respiratory symptoms. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.			
TALC & FERRIC OXIDE & MANGANESE SESQUIOXIDE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound.			
Acute Toxicity				
Acute Toxicity Skin Irritation/Corrosion	×	Carcinogenicity Reproductivity	X	
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×	
Respiratory or Skin	→	STOT - Repeated Exposure	x	
sensitisation Mutagenicity	×	Aspiration Hazard	X	
Mutagementy	**	Aspiration nazaru		

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
PD Stain Color Vial Terra Cotta	Not Available	Not Available	Not Available	Not Available	Not Available

Version No: 1.1 Page 7 of 9 Issue Date: 04/22/2020 Print Date: 04/22/2020

PD Stain Color Vial Terra Cotta

	l					
	ENDPOINT	TEST DURATION (HR)	SPECIES	SPECIES VALU		SOURCE
	LC50	96	Fish	Fish 89-581.016		2
talc	EC50	96	Algae or other aquatic plants	7-202	.7mg/L	2
	NOEC	720	Crustacea	1-459	.798mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	I	VALUE	SOURCE
	LC50	96	Fish	Fish 0.05mg/L		2
ferric oxide	EC50	48	Crustacea	Crustacea 5.11mg/L		2
	EC50	72	Algae or other aquatic plants	Algae or other aquatic plants 18mg/L		2
	NOEC	504	Fish	1	0.52mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES		VALUE	SOURCE
manganese sesquioxide	Not Available	Not Available	Not Available	 	Not Available	Not Available
Legend:	V3.12 (QSAR) -	Aquatic Toxicity Data (Estimated) 4.	HA Registered Substances - Ecotoxicological Info US EPA, Ecotox database - Aquatic Toxicity Data 1 (Japan) - Bioconcentration Data 8. Vendor Data	5. ECETOC Aq	-	

For Metal

Atmospheric Fate - Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air.

Environmental Fate: Environmental processes, such as oxidation, the presence of acids or bases and microbiological processes, may transform insoluble metals to more soluble ionic

For Manganese and its Compounds:

Environmental Fate: Manganese is a naturally occurring element in the environment occurring as a result of weathering of geological material. It also occurs from its use in steel manufacture/ coal mining.

Environmental Fate: Isothiazolinones are antimicrobials used to control bacteria, fungi, and for wood preservation and antifouling agents. They are frequently used in personal care products such as shampoos and other hair care products, as well as certain paint formulations.

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air	
	No Data available for all ingredients	No Data available for all ingredients	

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their

- Product / Packaging disposal
- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Version No: 1.1 Page 8 of 9 Issue Date: 04/22/2020 Print Date: 04/22/2020

PD Stain Color Vial Terra Cotta

Safety, health and environmental regulations / legislation specific for the substance or mixture

TALC IS FOUND ON THE FOLLOWING REGULATORY LISTS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

US ACGIH Threshold Limit Values (Spanish)

US ACGIH Threshold Limit Values (TLV)

US AIHA Workplace Environmental Exposure Levels (WEELs)

US NIOSH Recommended Exposure Limits (RELs)

US NIOSH Recommended Exposure Limits (RELs) (Spanish)

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US OSHA Permissible Exposure Levels (PELs) - Table Z3

US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)

US OSHA Permissible Exposure Limits - Annotated Table Z-3 (Spanish)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

FERRIC OXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US ACGIH Threshold Limit Values (Spanish)

US ACGIH Threshold Limit Values (TLV)

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

US NIOSH Recommended Exposure Limits (RELs) (Spanish)

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

MANGANESE SESQUIOXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US ACGIH Threshold Limit Values (Spanish)

US ACGIH Threshold Limit Values (TLV)

US AIHA Workplace Environmental Exposure Levels (WEELs)

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs) (Spanish)

US OSHA Permissible Exposure Levels (PELs) - Table Z1

US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No

Version No: **1.1** Page **9** of **9** Issue Date: **04/22/2020**

PD Stain Color Vial Terra Cotta

Print Date: **04/22/2020**

Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

None Reported

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (talc; ferric oxide; manganese sesquioxide)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (manganese sesquioxide)
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	04/22/2020
Initial Date	04/23/2020

CONTACT POINT

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

^{**}PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES**